

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

SeraSilk EL 81

1. IDENTIFICATION

A. Product name

- SeraSilk EL 81

B. Recommended use and restriction on use

- General use : Cosmetics
- Restriction on use : Cosmetics

C. Manufacturer / Supplier / Distributor information

○ Manufacturer information

- Company name : KCC Silicone Corporation
- Address : 801, Gwahak-ro, Bongdong-eup, Wanju_Gun, Jeollabuk-do
- Emergency telephone number : 82-63-260-1700

○ Supplier/Distributor information

- Company name : KCC Silicone Corporation
- Address : 801, Gwahak-ro, Bongdong-eup, Wanju_Gun, Jeollabuk-do
- Emergency telephone number : 82-63-260-1700

2. HAZARD IDENTIFICATION

A. GHS Classification

- Flammable liquids : Category3
- Aspiration hazard : Category1

B. GHS label elements

○ Hazard symbols



○ Signal words

- Danger

○ Hazard statements

- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways

○ Precautionary statements

1) Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P331 Do NOT induce vomiting.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated	Dodecane;N-Dodecan;Adakane 12;Dodecan;	93685-81-5	64 ~ 71
Siloxanes and Silicones, di-Me, hydroxy-terminated	Siloxanes and silicones, dimethyl, hydroxy terminated ; Di methyl polysiloxane hydroxy ; Methyl hydroxy terminated siloxane ; Poly(dimethylsiloxane), hydroxy-terminated ;	70131-67-8	13 ~ 20
Siloxanes and silicones, di-Me, Me hydrogen, reaction products with vinyl group-terminated di-Me siloxanes	Not available	156065-02-0	13 ~ 20

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Flammable liquid and vapour
- May be fatal if swallowed and enters airways

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.
- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- ACGIH TLV
 - Not applicable
- OSHA PEL

- Not applicable

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

- Respiratory protection
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Consider warning properties before use.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Eye protection
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Hand protection
 - Wear appropriate chemical resistant glove.
- Skin protection
 - Wear appropriate chemical resistant protective clothing.
- Others
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(paste)
- Color	Transparent
B. Odor	Odorless
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-81°C(Isododecane)°C
F. Initial Boiling Point/Boiling Ranges	176°C
G. Flash point	43°C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	Min : 0.5%, Max : 4% (Isododecane)
K. Vapour pressure	1 hPa(20°C, Isododecane)
L. Solubility	0,0001 g/1(Water, Isododecane)
M. Vapour density	5.9 (Isododecane)
N. Specific gravity(Relative density)	0.74kg/L(20°C, Isododecane)
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	410°C(Isododecane)°C
Q. Decomposition temperature	Not available
R. Viscosity	130,000 cP

S. Molecular weight	Not available
---------------------	---------------

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid: Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Sparks, flames, static electricity, strong acids and base substances

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- ☐ Respiratory tracts
 - May be fatal if swallowed and enters airways
- ☐ Oral
 - Not available
- ☐ Eye-Skin
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- ☐ Acute toxicity
 - * Oral
 - Product (ATEmix) : >5000mg/kg
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : LD50 > 5000 mg/kg Rat (Read across EC 923-037-2)(OECD TG 401, GLP)(ECHA)
 - * Dermal
 - Product (ATEmix) : >5000mg/kg
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : LD50 > 2200 ~ 2500 mg/kg bw Rabbit (Read across EC No. 921-728-3) (ECHA)
 - * Inhalation
 - Product (ATEmix) : Not available
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : Vapour LC50 > 4.951 mg/L 4hr Rat (Read across EC 920-901-0)(OECD TG 403)(ECHA)
- ☐ Skin corrosion/irritation
 - Not available
- ☐ Serious eye damage/irritation
 - Not available
- ☐ Respiratory sensitization
 - Not available
- ☐ Skin sensitization
 - Not available
- ☐ Carcinogenicity
 - * IARC
 - Not available

- * OSHA
 - Not available
- * ACGIH
 - Not available
- * NTP
 - Not available
- * EU CLP
 - Not available

- ☐ Germ cell mutagenicity
 - Not available
- ☐ Reproductive toxicity
 - Not available
- ☐ STOT-single exposure
 - Not available
- ☐ STOT-repeated exposure
 - Not available
- ☐ Aspiration hazard
 - May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- ☐ Fish
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : LL50 > 100 mg/L 96hr Danio rerio (Read across EC 942-924-5)(OECD TG 203,GLP)(ECHA)
- ☐ Crustaceans
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : EL50 > 100 mg/L 48hr Daphnia magna (Read across EC 940-727-9)(OECD TG 202,GLP)(ECHA)
- ☐ Algae
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : EL50 > 100 mg/L 72hr Raphidocelis subcapitata (Read across EC 942-924-5)(OECD TG 201,GLP)(ECHA)

B. Persistence and degradability

- ☐ Persistence
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : log Pow 5.6~6.65(20°C,pH7)(ECHA)
- ☐ Degradability
 - Not available

C. Bioaccumulative potential

- ☐ Bioaccumulative potential
 - Not available
- ☐ Biodegradation
 - [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : Not readily biodegradable, 8.74 % degradation (CO2 evolution) 31day (Read across 64742-47-8)(EPA OTS 796.3100)(ECHA)

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration

- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- 1993

B. Proper shipping name

- FLAMMABLE LIQUID, N.O.S.(Pentamethylheptane)

C. Hazard Class

- 3

D. IMDG CODE/IATA DGR Packing group

- III

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

○ POPs Management Law

- [Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated] : Not applicable
- [Siloxanes and Silicones, di-Me, hydroxy-terminated] : Not applicable
- [Siloxanes and silicones, di-Me, Me hydrogen, reaction products with vinyl group-terminated di-Me siloxanes] : Not applicable

○ Information of EU Classification

- * Classification
 - Not applicable

○ U.S. Federal regulations

- * OSHA PROCESS SAFETY (29CFR1910.119)
 - Not applicable
- * CERCLA Section 103 (40CFR302.4)
 - Not applicable
- * EPCRA Section 302 (40CFR355.30)
 - Not applicable
- * EPCRA Section 304 (40CFR355.40)
 - Not applicable
- * EPCRA Section 313 (40CFR372.65)
 - Not applicable

○ Rotterdam Convention listed ingredients

- Not applicable

☐ Stockholm Convention listed ingredients

- Not applicable

☐ Montreal Protocol listed ingredients

- Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2019-05-08

C. Revision number and Last date revised

- 5 times, 2026-03-03

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).